



ARMSTRONG METALWORKS™ LAY-IN

- Available in a variety of edge details for installation on Prelude 24mm, Suprafine or Silhouette 15mm suspension system
- Diversity of design and application
- Easily assembled and fully demountable
- Cost effective ceiling solution
- Tiles are easily lifted out by hand, allowing full and easy access to the ceiling void

Panel Options	Board	Tegular 8	Microlook 8	
Edge details	 24mm Exposed Grid	 24mm Exposed Grid	 15mm Exposed Grid	
Material	Galvanized Steel (Aluminum optional)			
Patterns *Perforated panels feature an unperforated border and include acoustical fleece.	 Non Perforated (M1)	 Micro Perforated (M2) 1.5mm Ø 19% Open Area	 Micro Perforated (M9) 1.5mm Ø 9.5% Open Area	 Standard Perforated (M10) 2.5mm Ø 16% Open Area
Dimensions (mm)	600 x 600 1200 x 600 (Other sizes available on request)			
Suspension System	Standard Peakform Prelude 24mm or Suprafine 15mm Suspension System			
Weight	4.6 kg/m ²			
Colour	Polyester Powder Coated – Global White Wood Effects Available by Request			
Sound absorption	NRC 0.70 (M2) / NRC 0.75 (M9) / NRC 0.80 (M10) - Perforated Option with fleece, without additional infill. Contact your local sales representative for test data.			
Sound attenuation	Approximately 18 dB (without additional infill). Optional: High Attenuation Performance Up to 38dB (NRC 0.60) with additional mineral infill.			
Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7			
Handling	100% upward demountable without tooling.			
Durability				
Cleanability				

All sizes are nominal. Product availability may vary.



SCAN & EMAIL ME

MAIN OFFICE

DAVAO OFFICE