





















# ARMSTRONG BIOGUARD PLAIN

- Specially developed for controlled environment requiring excellent cleanability and resistance to disinfectants
- Anti-microbial performance provides protection against bio-contamination
- Durable, Washable, Smooth surface
- Good sound antenuation performance
- Improved water repellent back coating
- High light reflective finish – 89%
- Humiguard Plus® (RH95) Performance



# ARMSTRONG BIOGUARD PLAIN

Panel Options	Board	Tegular 24	Bevelled Tegular 15
 <b>Edge details</b>	 24mm Tee Grid	 24mm Tee Grid	 15mm Tee Grid
 <b>Thickness (mm)</b>	15mm	15mm	15mm
 <b>Dimensions (mm)</b>	600 x 600	8682	8684
	1200 x 600	8681	8685
 <b>System</b>	24mm exposed grid systems fully demountable	24mm exposed grid systems fully demountable	15mm exposed grid systems fully demountable
 <b>Weight</b>	3.3 kg/m <sup>2</sup>		
 <b>Colour</b>	Global White		
 <b>Sound absorption</b>	N/A		
 <b>Sound attenuation</b>	33 dB		
 <b>Fire reaction</b>	CLASS 0/1 based on BS 476 Part 6 & 7		
 <b>Light reflectance</b>	≤ 89%		
 <b>Thermal conductivity</b>	$\lambda = 0.060 \text{ W/mk}$		
 <b>Humidity resistance</b>	RH95		
 <b>Clean room</b>	Class 5 as per ISO 14644-1		
<b>Durability</b>			
<b>Cleanability</b>			
 <b>Sustainability</b>	 ≤36%	Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification	



SCAN & EMAIL ME

## Contact