KNAUFGEILINGSolutions





DUNE

- Legacy Armstrong DUNE 16mm features a microperforated, finely sanded surface to offer a smooth installed visual with good noise absorption
- Good sound absorption (NRC 0.50) and high sound attenuations (33 dB)
- Good light reflectance (85%)
- Humiguard Plus® (RH99) Performance



ARMSTRONG DUNE



| | Panel Options | Board | Tegular 24 | Bevelled Tegular 15 |
|-----------------|--------------------------|---|---|---|
| <u>↓</u> | Edge details | | | |
| | | 24mm Tee Grid | 24mm Tee Grid | 15mm Tee Grid |
| <u>↓</u> | Thickness (mm) | 16mm | 16mm | 16mm |
| mm (+++ +++> | Dimensions (mm) | | | |
| | 600 x 600 | 3643 | 3647 | 3651 |
| | 1200 x 600 | 3641 | 3645 | 3649 |
| | 24 x 24 x 7/11" | 3642 | 3646 | 3650 |
| | 24 x 48 x 7/11" | 3640 | 3644 | _ |
| | System | 24mm exposed grid systems fully demountable | 24mm exposed grid systems fully demountable | 15mm exposed grid systems fully demountable |
| √Kg \\ | Weight | 3.8 – 4.00 kg/m² | | |
| | Colour | Global White | | |
| ₹ | Sound absorption | NRC 0.50 | | |
| ₹ | Sound attenuation | ≤ 33 dB | | |
| F | Fire reaction | CLASS 0/1 based on BS 476 Part 6 & 7 | | |
| ✓ • | Light reflectance | ≤ 85% | | |
| | Thermal conductivity | λ = 0.052-0.057 W/mk | | |
| 4,4 | Humidity resistance | RH99 | | |
| | Durability Cleanability | | | |
| | | | | |
| % \$ 80 14021 | Sustainability | Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification ✓ 33% | | |





