





ARMSTRONG ULTIMA

- Specially developed for Grade-A workspace application requiring acoustic flexibility
- Best in class durability with Clean Room performance
- Total Acoustics Performance (NRC+CAC) provides excellent sound attenuation and absorption, improving room to room privacy, quieter space, increase concentration, productivity and efficiency
- High light reflective finish up to 88%
- Humiguard Plus® (RH99) Performance



ARMSTRONG ULTIMA



	Panel Options	Board	Tegular 24	Tegular 15/90	K2C2 / SL2
<u></u>	Edge details	24mm Tee Grid	24mm Tee Grid	15mm Tee Grid	24mm Tee Grid
<u>↓</u>	Thickness (mm)	19mm	19mm	19mm	19mm
mm (m m)	Dimensions (mm)				
l''''1	600 x 600	1001	1003	1005	_
	1200 x 600	1002	1004	1006	Available upon request
	System	24mm exposed grid systems fully demountable	24mm exposed grid systems fully demountable	15mm exposed grid systems fully demountable	Semi-concealed grid system: 24mm exposed long ends with concealeed short end fully demountable
√Kg \\	Weight	5.0 kg/m ²			
	Colour	Global White			
*	Sound absorption	NRC 0.70			
新	Sound attenuation	39 dB			
T	Fire reaction	CLASS 0/1 based on BS 476 Part 6 & 7			
∕ •	Light reflectance	≤ 88%			
	Thermal conductivity	$\lambda = 0.060 \text{ W/mk}$			
4,4	Humidity resistance	RH99			
W	Clean room	ISO 3 as per ISO 14644-1			
	Durability				
	Cleanability				
2% EN ISO 14021	Sustainability	Knauf Armstrong provides the widest range of products that have been third party tested and certified by industry leading Eco-classification			





MAIN OFFICE

DAVAO OFFICE