



PEAKFORM SUPRAFINE XL 15mm Exposed Tee System

BENEFITS

- Hot dipped galvanized coating inhibits red rusting better than electrogalvanized, painted or plated systems.
- System is engineered and designed to coordinate with Armstrong & Thermanex Ceilings.
- PeakForm patented main beam profile for installation with Suprafine XL stab-end cross tees.
- The PeakForm bulb design increases strength and stability for improved performance.
- Superlock main beam clip engineered for a strong, secure connection and fast accurate alignment confirmed with an audible click.
- Easy to cut thanks to the PeakForm bulb design.
- Rotary stitched for additional torsional strength and extra stability during installation.
- Slots at 100mm centres for more flexibility (3600mm long main beam).
- Easy to remove and relocate.
- Faster and easier insertion/installation of XL cross tees.
- Tighter tee to tee connection.
- It has better load carrying capability.

Material

Double-web hot dipped galvanized steel

Surface Finish

Baked polyester paint

Cross Tee/Main Beam Interface

XL-Override

End Detail

PeakForm main beam:
Superlock staked-on clip
XL Cross Tee: Staked-on clip

Profile

Exposed tee system

Classification















Intermediate duty ID
Light duty LD

Colour Selection

White (WH)

PEAKFORM SUPRAFINE XL

15mm Exposed Tee System

Suprafine XL43							
	Item Number	Description	Dimensions				
			Root Spacing	Length	Height	Width	
		BP754042*	3600mm Main Beam	100mm	3600mm	43mm	15mm
		BP753042	1200mm Cross Tee	600mm	1200mm	43mm	15mm
		BP752042	600mm Cross Tee	-	600mm	43mm	15mm
Suprafine XL32							
		BP7542102**	3000mm Main Beam	150mm	3000mm	32mm	15mm
		BP7530102	1200mm Cross Tee	600mm	1200mm	32mm	15mm
		BP753061	1200mm Cross Tee	600mm	1200mm	27mm	15mm
		BP7520102	600mm Cross Tee	-	600mm	32mm	15mm
		BP752061	600mm Cross Tee	-	600mm	27mm	15mm
Seismic Grid							
		BPT1945H	3000mm Angle Molding	-	3000mm	19mm	19mm
		BPT2222H	3000mm Angle Molding	-	3000mm	22mm	22mm
		BP784203	3000mm Shadow Molding	-	3000mm	19 x 7 x 7 x 14mm	
	Sustainability			25%			

Note: Hanger Spacing 1200mm, Load: * 19.7kg/m ID, ** 8.52kg/m LD

