

# EUROBOARD

## JOINT COMPOUND



### Euroboard Joint Compound

Dry wall joint treatment are crucial things for perfect gypsum finishing. Only the best materials can give right solution.

Euroboard Joint Compound is the right answer. Used as final touch up coats in interior gypsum application, it is an ideal material for embedding fastener, corner beads, and gypsum panel surfaces skim coating.

It is also applicable for covering wall cracks, unsmooth surfaces, and tiny holes on the wall.

It is special for interior using only.





## Preparation



Always use clean water and clean container and tools.



Using dirty containers / water / tools may affect setting time and set strength.



Pour Euroboard Joint Compound slowly into water and allow compound to soak for 1 - 3 minutes before



Mix only enough compound for 25 minutes working time.



Mix manually or with a hand mixer until a smooth mixture is attained. Avoid stirring for too long as it will fasten drying time.



Every time the mixing is done, avoid possibility of mixing with the previous mixture or other types of mixture as this will fasten the drying time.



Do not add other materials into the mixture as it will impair the performance of this product.

### Caution

Sanding dust (from out standing) may cause eye, nose, throat or upper respiratory irritation, long term breathing of large amounts of mica may cause lung disease. Use wet sanding technique to avoid creating dust if dry sanded, wear a NIOSH approved dust mask. Do not take internally. The use of safety glasses is recommended. Keep out of children's reach.

Note : The company reserve the rights to revise any data without prior notice.

\* Terms and condition apply

## Technical Data

**Working Time** : 15 minutes

**Bonding Time** : 25 minutes

**Mixing Ratio** : 2 parts of compound to 1.4 part of clean water in kg

**Storage** : Stored in a dry location and protected from temperature extremes.  
*Once the bag has been opened can shorten the life of the product.*

**Shelf Life** : 9 - 12 months (when stored correctly)

**Packaging** : 1 Bag 20 Kg

## Product Usage

- Fixing and bonding cornice to plasterboard and wall.
- Can be used directly to concrete wall avoid crack because of high bonding strength.

## Application

1. Checking application location.
2. Pour Euroboard Joint Compound powder to container which contains water with 2,8 : 1 ratio.
3. Mix the compound thoroughly, ensure that there are no bubbles through the process and the compound will be ready to use.

## Application Area

- Joint Compound between gypsum board
- As cornice adhesive
- Holes and cracks on wall filler
- Partition
- Ceiling



SCAN & EMAIL ME